LAMINATE FLOORING

Installation Guide

Proper installation of our products is needed to ensure long lasting reliability and durability. Ensure to use our floor coverings for indoors only.

Laminated Wood is an eco-friendly alternative to natural wood flooring, it's cost effective and easy to install as well; but like natural wood it can be damaged by water, thus ensure that our laminated wood is used only on the following areas:

Approved locations



- Bedroom
- Living Room
- Dining Room



Unapproved locations


- Comfort room/washroom
- Highly moist areas
- Balcony/Terrace
- Outdoor area



Steps on how to install Laminated wood planks

- 1) The floor should be even and nearly flat, it should also be clean and clear of any debris to ensure a proper finish.
- 2) Unbox the planks to the work area and let it be exposed to the room for about 48-72 hours for acclimatization.
- 3) Acclimatization" is an additional step for laminated wood wherein the material adapts and expands by a few centimeters depending on the humidity and temperature of the room.
- 4) Clean the floor and place the 2mm HDF or high-density foam included on the purchase and place the laminated wood above the foam. This installation process is called "floating method" as the planks literally floats on the foam.







LAMINATE FLOORING

- 5) Place the planks and carefully attach each using the **clip-lock edges**. Use a **Jigsaw power tool or Metal hand saw** to cut the planks as needed.
- 6) Ensure a **10-12mm perimeter gap** between the edges of the room. Use a Silicone sealant, end cap or base board to cover this gap.
- 7) Install an **End cap**, **Reducer** or **T-mold** using a **liquid nail** if the laminated flooring will end or be place along ceramic tiles, carpet or a different flooring like vinyl or **AUC**.
- 8) After installation, sweep the floor, and use a damp cloth or mop to clean the laminate flooring for a clean and desirable finish.
- 9) For care and maintenance, only use damp cloth or a clean damp mop. Never use wax, varnish, or any bleach products as it may damage the planks.

